



V-RAD SELECT

Quick adjust torque with equal power in forward and reverse

V-RAD Select electric torque wrench is used for the installation or removal of heavy-duty fasteners where accuracy, power, and safety are required. Quick adjust torque settings. Equal power in forward and reverse.

ELECTRIC



FEATURES

- Torque ranges up to 3,000 ft. lbs./ 4,000 Nm
- Digital torque settings to increase and decrease the value by 10 ft. lbs./ 10 Nm
- Available in both 120V or 230V

CASE

Durable, light weight, shock proof. Designed to protect your RAD investment.



V-RAD SELECT 1000



V-RAD SELECT 1500



V-RAD SELECT 3000

IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (ft. lbs.) LOW	TORQUE (ft. lbs.) HIGH	RPM	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
25628	V-RAD SELECT 1000	0.75"	100	1000	8.8	8.6	12"	2.5"	2.9"	8"
25629	V-RAD SELECT 1500	1.0"	150	1500	5.7	9.6	12.25"	2.7"	2.9"	8"
25631	V-RAD SELECT 3000	1.0"	300	3000	2.7	13.7	13.5"	3.1"	3.1"	8"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE (Nm) LOW	TORQUE (Nm) HIGH	RPM	WEIGHT (Kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
25633	V-RAD SELECT 1400	0.75"	140	1400	8.8	3.9	305	64	74	203
25634	V-RAD SELECT 2000	1.0"	200	2000	5.7	5.9	311	69	74	203
25636	V-RAD SELECT 4000	1.0"	400	4000	2.7	6.2	343	79	79	203

Accuracy of +/-5%, Repeatability of +/-2%



ADVANCED BOLTING SOLUTIONS - SAUDI ARABIA

O/o Diversified Lines Petroleum Services Co., Abu Al Hasan Al Zahrawy Street,
Khalidiya Shumaliya, Dammam - 32231, Saudi Arabia
Phone: (+966) 509775727 | Email: mrashid@absgroup-arabia.com

www.absgroup-arabia.com

