

E-RAD BLU



90 DEGREE*



OFFSET*

*Only available on certain models.



**SHOWN WITH OPTIONAL
MOUNTING ACCESSORY**

CASE

Durable, light weight,
shock proof. Designed
to protect your
RAD investment.



Ability to use different handles with controller case

ELECTRONIC



E-RAD BLU precision torque wrench tools are designed to provide a high degree of accuracy (+/- 2.8%) and repeatability (+/- 2%). Using a patented gearbox design and the precision of an electric AC Servo motor, these tools deliver smooth continuous torque. Best of all, it's the most affordable system on the market.

FEATURES

- Advanced data logging and tool management features
- Military grade single cable and connector system
- Available in a 90-degree gearbox
- LED indicator lights (pass/fail)
- Push-button select torque
- Lightweight and ergonomic pistol grip


TOUCH CONTROL CASE

- Easy to use interface
- Pre-sets for torque and angle adjustments
- Quick error-free torque and angle adjustments
- Complete recalibrations
- Data logging with export to laptop



RAD SMART SOCKETS™

RAD SMART SOCKETS™ can connect to the E-RAD BLU tool via Bluetooth® technology. This combination allows you to automatically calibrate your E-RAD BLU to any joint!



IMPERIAL

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	TORQUE HIGH (ft. lbs.)	RPM 120V	RPM 230V	WEIGHT (lbs.)	DIMENSION A	DIMENSION B	DIMENSION C	DIMENSION D
21980	E-RAD BLU 700	0.75"	100	700	15	30	12	13.25"	2.5"	3.0"	10.65"
24161	E-RAD BLU 1500	1.0"	200	1500	8	16	13	13.28"	2.7"	3.0"	10.65"
21981	E-RAD BLU 2500 COMP	1.0"	250	2500	4.9	10	18	14.8"	3.0"	3.0"	10.65"
24221	E-RAD BLU 2500 COMP-90 Degree	1.0"	250	2500	6	12	18	9.65"	3.0"	3.1"	11.83"
21982	E-RAD BLU 3000	1.0"	500	3000	4.1	8.5	23.5	16.75"	3.4"	3.5"	11.29"
21983	E-RAD BLU 6000	1.5"	1000	6000	2.1	4.5	29	16.5"	4.0"	3.5"	11.29"
21984	E-RAD BLU 7500	1.5"	1500	7500	1.5	3	33	17.0"	4.25"	4.25"	11.29"
24234	E-RAD BLU 11K*	1.5"	3000	11000	1.2	2.3	43	18.3"	5.0"	5.0"	11.29"

METRIC

PART NUMBER	TOOL MODEL	DRIVE SIZE	TORQUE LOW	TORQUE HIGH (N m)	RPM 120V	RPM 230V	WEIGHT (kg)	DIMENSION A (mm)	DIMENSION B (mm)	DIMENSION C (mm)	DIMENSION D (mm)
21985	E-RAD BLU 950-M	0.75"	135	950	15	30	5.5	340	65	78	275
24162	E-RAD BLU 2000-M	1.0"	270	2000	8	16	5.9	337	69	78	275
21986	E-RAD BLU 3400-M COMP	1.0"	340	3400	4.9	10	7.6	380	76	78	275
22434	E-RAD BLU 3400-90-M Degree	1.0"	340	3400	6	12	8.3	210	76	78	300
21987	E-RAD BLU 4000-M	1.0"	675	4000	4.1	8.5	11	430	86	88	287
21988	E-RAD BLU 8000-M	1.5"	1350	8000	2.1	4.5	13.5	419	100	100	287
21989	E-RAD BLU 10K-M	1.5"	2000	10000	1.5	3	15	432	105	105	287
24224	E-RAD BLU 15K-M*	1.5"	4000	15000	1.2	2.3	20	465	127	127	287

Accuracy of +/-2.8%, Repeatability of +/-2% | *Also available in a 2.5" square drive.



ADVANCED BOLTING SOLUTIONS - SAUDI ARABIA

C/o Diversified Lines Petroleum Services Co, Abu Al Hasan Al Zahrawy Street,
Khalidiya Shumaliya, Dammam - 32231, Saudi Arabia
Phone: (+966) 509775727 | Email: mrashid@absgroup-arabia.com

www.absgroup-arabia.com

